


THREE PHASE & MULTIPLE MPPT

ET K100TL-8MG3/ K110TL-9MG3/ET K125TL-9MG3

Application: Commercial & Industrial Sites



FEATURE



Superior Performance

- Maximum efficiency of 98.8%.
- Large string current, compatible with large PV modules.
- 9 MPPT, fuse-free design technology.



High Reliability

- IP66 protection level for outdoor installation.
- Replaceable DC/AC Type II SPD.
- Optional: AFCI, Night SVG, I/V detection, and integrated PID.



Intelligent Maintenance

- Power consumption monitoring.
- Remote configuration and upgrade.
- Quick commissioning via mobile app.
- String level current detection.

Technical Specifications

Model	ET K100TL-8MG3	ET K110TL-9MG3	ET K125TL-9MG3
Efficiency			
Max. Efficiency	98.50%	98.60%	98.80%
European Efficiency	98.00%	98.20%	98.20%
Input (PV)	1100V		
Max. Input Voltage	1.5		
Max. PV Configuration	620V		
Max. Input Current	5*32A/3*40A		6*32A/3*40A
Max. Short Circuit Current	5*45A/3*50A		6*45A/3*50A
Start Input Voltage/ Min. Operating Voltage	250V / 200V		
MPPT Operating Voltage Range	200V-1000V		
Max. Number of PV Strings	8*2	9*2	
No. of MPPTs	8	9	
Output (Grid)			
Rated AC Active Power	100,000W	110,000W	125,000W
Max. AC Apparent Power	111,000VA	123,000VA	125,000VA
Max. AC Output Current	3*168.8A	3*187A	3*181A
Rated AC Voltage	380V/400V, 3W+N+PE		
AC Voltage Range*	320V-520V (Adjustable)		
Rated Grid Frequency	50Hz / 60Hz		
Grid Frequency Range**	45Hz-55Hz / 55Hz-65Hz (Adjustable)		
THDI	<3% (Rated Power)		
DC Current Injection	<0.5%In		
Power Factor	>0.99 Rated power (Adjustable 0.8 LD - 0.8 LG)		
Protection			
DC Switch	Yes		
Anti-Islanding Protection	Yes		
AC Overcurrent Protection	Yes		
AC Short Circuit Protection	Yes		
DC Reverse Protection	Yes		
Surge Arrester	DC Type II / AC Type II		
Insulation Detection	Yes		
Leakage Current Protection	Yes		
AFCI	Optional		
PID Recovery	Optional		
PV String Monitoring	Yes		
Consumption Monitoring	Optiona		
General			
Topology	Transformerless		
IP Rating	IP66		
Night Self Consumption	<10W (Standard)		
Cooling	Fan cooling		
Operating Temperature Range	-25℃-60℃		
Relative Humidity Range	0-100%		
Max. Operating Altitude	4000m		
Dimensions (W*H*D)	936mm*678mm*365mm		
Weight	91.5Kg		
HMI & COM			
Display	Wireless & APP+LED, LCD (Optional)		
Communication	RS485, Optional: WiFi / GPRS / LAN		
Certification			
Safety	IEC62109-1, IEC62109-2		
Grid Code	EC 61727/62116, VDE-AR-N 4105, CEI 0-21/16, UNE 206006/206007		
Warranty	5 Years		

Remarks:·①②The range of output voltage and frequency may vary depending on different grid codes.
Specifications are subject to change without advanced notice.