



SUN POWER

640–665 Watt
Mono-Bifacial Module

- IEC61215: 2021
IEC61730: 2016
TUV Rheinland Standard
- Lloyd'S Ariel Re
Solar Performance
Insurance
- ISO9001: 2015
Quality Management
System
- ISO14001:
Environmental
Management System
- CE: Europe Standard
- Inmetro Certificate
- Japan JP-AC



Feature



MBB Cell

More uniform current collecon capability, reducing the current heat loss of the internal cells.



Higher Output Power

The output power of 132 half-cells Monocrystalline modules is up to 665W



Harsh Environmental Adaptability

Strict salt spray and ammonia corrosion test by the third party.



Low Light Features

Higher performance under low light environment.



LID Free


N-type solar cell has no LID naturally which can increase power generation.



Load Capacity

Mechanical load tests including wind load 2400 Pa and snow load 5400 Pa.

Mechanical Diagrams



Specifications

Weight	38.5kg
Dimension	2384mm*1303mm*35mm
Cell Dimension	210*105mm
Cell Amount	66*2 pcs
Maximum System Voltage	1500V
Junction Box	IP68
Type of the front glass	2.0mm Coated ultra clear glass
Type of the back glass	2.0mm Heat-strengthened glass
Frame	Aluminum Alloy
Cable	4mm ² , +300, -300mm/±1300mmLength can be customized
Connector	MC4 compatible
Application Level	Class A

Temperature Characteristics

NMOT	45±2°C
Temp Coefficient of ISC	+0.05%/°C
Temp Coefficient of VOC	-0.28%/°C
Temp Coefficient of Pmax	-0.34%/°C

Packing Configuration

Modules/Pallet	31 Pieces
Packaging Description	18 Pallets, Total=(31+31)x9=558 Pieces
Modules/40'Container	558 Pieces

Electrical Parameters At Stc

Module Type	HS640-MHG-D	HS645-MHG-D	HS650-MHG-D	HS655-MHG-D	HS660-MHG-D	HS665-MHG-D
Power	640W	645W	650W	655W	660W	665W
Open Circuit Voltage	45.18V	45.38V	45.58V	45.78V	45.98V	46.18V
Short Circuit Current	18.06A	18.11A	18.16A	18.21A	18.26A	18.31A
Maximum Power Voltage	37.21V	37.41V	37.61V	37.81V	38.01V	38.21V
Maximum Power Current	17.20A	17.24A	17.28A	17.32A	17.36A	17.40A
Module Efficiency	0.206	0.2076	0.2092	0.2109	0.2125	0.2141

* Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

Electrical Parameters At Bnpi

Power	701W	706W	712W	717W	723W	730W
Open Circuit Voltage	45.18V	45.38V	45.58V	45.78V	45.98V	46.3V
Short Circuit Current	19.39A	19.45A	19.53A	19.58A	19.66A	20.14A
Maximum Power Voltage	37.21V	37.41V	37.61V	37.81V	38.01V	38.2V
Maximum Power Current	18.84A	18.87A	18.93A	18.96A	19.02A	19.13A

*Rear side power gain: The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure,height, tilt angle etc.)and albedo of the ground.



Electrical Parameters At Nmot

Power	483W	487W	491W	495W	499W	503W
Open Circuit Voltage	41.93V	42.11V	42.3V	42.48V	42.67V	43.60V
Short Circuit Current	14.81A	14.85A	14.89A	14.93A	14.97A	15.01A
Maximum Power Voltage	34.49V	34.68V	34.86V	35.05V	35.24V	35.45V
Maximum Power Current	14.03A	14.06A	14.09A	14.13A	14.16A	14.19A
Module Efficiency	0.1555	0.1568	0.1582	0.1594	0.1606	0.1619

* Under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

IV Characteristics

HS665-MHG-D



Maximum Rating

Power selection	0~+5W
Measuring uncertainty of Pm	0~±3%
Operating Temperature	-40°C~+85°C
Wind Load/Snow Load	2400pa/5400pa
Fuse Current	30A

15
YEARS

Quality
Warranty

25
YEARS

Power
Warranty